

**autOTEK®**

**2011 PRODUCT LINE**

ATX AMPLIFIERS	PERFORMANCE
ATX1000.2	2 x 250 @ 4 OHMS, 2 x 500 @ 2 OHMS - 1 x 1000 WATTS @ 4 OHMS
ATX1600.2	2 x 400 @ 4 OHMS, 2 x 800 @ 2 OHMS - 1 x 1600 WATTS @ 4 OHMS
ATX3000.2	2 x 750 @ 4 OHMS, 2 x 1500 @ 2 OHMS - 1 x 3000 WATTS @ 4 OHMS
ATX950.4	4 x 120 @ 4 OHMS, 4 x 240 @ 2 OHMS - 2 x 475 @ 4 OHMS
ATX1200.4	4 x 150 @ 4 OHMS, 4 x 300 @ 2 OHMS - 2 x 600 @ 4 OHMS
ATX2000.1	1 x 500 @ 4 OHMS, 1 x 1000 @ 2 OHMS, 1 x 2000 @ 1 OHM A/B Class

- New Flat Panel Heat Sink Design
- Military PCB Design
- SEPP A/B Analog Class
- 4/2 Ohm Stable
- Multi Channel Configurable 4/3/2/1
- PWM Power Supply
- Fully Adjustable 12 dB Crossovers
- Input Sensitivity From .2 to 5 V
- High and Low Level Inputs
- Bass Remote Included with P1-2000.1
- Subsonic Filter, Bass EQ



ATX SPEAKERS	PERFORMANCE
ATX46CX	4 X 6" CO-AXIAL SPEAKER 500 WATTS MAXX 50 WATTS NOMINAL
ATX5768CX	5 X 7 - 6 X 8" CO-AXIAL SPEAKER 500 WATTS MAXX 50 WATTS NOMINAL
ATX6.5CX	6.5" Co-Axial Speaker 800 Watts Maxx 60 Watts Nominal
ATX693T	6 x 9" Three-Way 1000 Watts Maxx 70 Watts Nominal
ATX6.2C	6.5" Two-Way Component with In-Line Crossover 800 Watts Maxx 60 Watts Nominal

- Impact Resistant Tweeter Elements
- Neo-Mylar Soft Dome Tweeter
- Installation hardware Included
- Polypropylene Cones
- Spade Style Speaker Terminals
- UV Resistant Rubber Surround
- High Mid-Bass Impact
- Anti-Resonant Stamped Steel Basket
- Wide Nominal Power Range



ATX SUBWOOFERS	PERFORMANCE
ATX12D4	12" DVC 4 Ohm Subwoofer 350 RMS 700 Watts Maxx

- 12-Inch DVC Subwoofer
- Dual 4-Ohm Voice Coils
- High Energy Magnet With Rubber Motor Wrap
- Non-Pressed Pulp Paper Cone
- Ultra Rigid Stamped Steel Basket
- Multi-Layer High-Temp VC
- Front-Plate & Voice-Coil Cooling
- Stitched And Glued Bond For Surround To Cone
- Foam Surround



MEAN MACHINE AMPLIFIERS	PERFORMANCE
M1600.2	2 x 400 @ 4 OHMS, 2 x 800 @ 2 OHMS - 1 x 1600 WATTS @ 4 OHMS
M3200.2	2 x 800 @ 4 OHMS, 2 x 1600 @ 2 OHMS - 1 x 3200 WATTS @ 4 OHMS
M1000.4	4 x 125 @ 4 OHMS, 4 x 250 @ 2 OHMS - 2 x 500 WATTS @ 4 OHMS
M1400.4	4 x 175 @ 4 OHMS, 4 x 350 @ 2 OHMS - 2 x 700 WATTS @ 4 OHMS
M2000.4	4 x 250 @ 4 OHMS, 4 x 500 @ 2 OHMS - 2 x 1000 WATTS @ 4 OHMS
M1500.1	1 x 325 @ 4 OHMS, 1 x 750 @ 2 OHMS - 1 x 1500 WATTS @ 1 OHM MONO
M2500.1	1 x 625 @ 4 OHMS, 1 x 1250 @ 2 OHMS - 1 x 2500 WATTS @ 1 OHM MONO
M4000.1	1 x 1000 @ 4 OHMS, 1 x 2000 @ 2 OHMS - 1 x 4000 WATTS @ 1 OHM MONO
MM SUBWOOFER	PERFORMANCE
M12D4	12" DVC 4 Ohm Subwoofer 500 Watts RMS 1000 Watts Maxx

- A/B Analog Class Amplification
- "Military Grade" PCB
- 4/2 Ohm Stable
- High Speed MOSFET Output Devices
- 4/2/1 Ohm Stable
- HF High Dissipation Heat Sink
- Multi Channel 4/3/2/1 Channel Configurable
- High Speed MOSFET Output Devices
- Variable Low Pass, High Pass, Band Pass
- RCA Inputs and Outputs
- Built-in system Diagnostics



SIREN FULL RANGE	PERFORMANCE
ATS6.5-4	6.5" 8 Ohm Full Range High Output Speaker - Sold as singles
ATS8	8" 8 Ohm Full Range High Output Speaker - Sold as singles
AT46-8	2" 100 Watt RMS Super Tweeter 8Ohms 102dB! Output

- Full Range High Output Speaker
- Sold as singles
- 1.5" Voice Coil
- 4 / 8 Ohm Single Voice Coil
- Spade Terminals
- Stamped Steel Basket
- 29 Oz. Magnet
- Treated Pressed Paper Cone
- Cloth "W" Surround
- Polished Aluminum Phase Plug
- Poly Cotton Spider



**SIREN**



**MAXXSONICS®**



MAXXSONICS  
Maxxsonics® USA, Inc.  
1290 Ensell Road  
Lake Zurich Illinois 60047 USA  
Phone: 847-540-7700  
FAXX: 847-540-9776

www.maxxsonics.com  
MB Quart,® Autotek,® Hifonics®  
and Crunch® USA are divisions of  
Maxxsonics® USA Inc.

Visit Us On The Web @  
[maxxsonics.com](http://maxxsonics.com)  
[myspace.com/maxxsonicsusa](http://myspace.com/maxxsonicsusa)  
[youtube.com/MaxxsonicsUSAInc](http://youtube.com/MaxxsonicsUSAInc)

©2011 Maxxsonics USA, Inc.  
All Rights Reserved  
Specifications And Designs Are Subject To Change Without Notice.